

Description

Fastener Length: 1/4", Thread: 4-40, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	642AS75221
Minimum Qty (MOQ):	40 EA
NSN:	5305-01-080-5719
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 642AS7522-1 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.169 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.183 Inches Nominal
Head Height:	0.107 Inches Nominal
Locking Feature:	Strip Threads
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Material:	Plastic Locking Feature
Material:	Steel Comp 302 Fastener Or Steel Comp 304 Fastener Or Steel Comp 304 Fastener
Material Document And Classification:	Qq-s-763 Cond B Fed Spec 1st Material Response Overall Or Qq-s-763 Cond B Fed Spec 2nd Material Response Overall Or Astm A582 Assn Std 3rd Material Response Overall
Surface Treatment:	Passivate Fastener
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/642AS7522-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.