

Description

Fastener Length: 1/4", Thread: 4-40, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 642AS75221 |
| Minimum Qty (MOQ): | 40 EA |
| NSN: | 5305-01-080-5719 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 642AS7522-1 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.169 Inches Minimum And 0.250 Inches Maximum |
| Fastener Length: | 0.219 Inches Minimum And 0.250 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.183 Inches Nominal |
| Head Height: | 0.107 Inches Nominal |
| Locking Feature: | Strip Threads |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 40 |
| Material: | Plastic Locking Feature |
| Material: | Steel Comp 302 Fastener Or Steel Comp 304 Fastener Or Steel Comp 304 Fastener |
| Material Document And Classification: | Qq-s-763 Cond B Fed Spec 1st Material Response Overall Or Qq-s-763 Cond B Fed Spec 2nd Material Response Overall Or Astm A582 Assn Std 3rd Material Response Overall |
| Surface Treatment: | Passivate Fastener |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Fastener |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/642AS7522-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.