

**Description**

Fastener Length: 3/16", Thread: 4-40, Thread Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	642AS75256
Minimum Qty (MOQ):	30 EA
NSN:	5305-01-080-9170
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N 642AS7525-6 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.106 Inches Minimum And 0.187 Inches Maximum
<b>Fastener Length:</b>	0.156 Inches Minimum And 0.187 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.205 Inches Minimum And 0.219 Inches Maximum
<b>Head Height:</b>	0.058 Inches Minimum And 0.068 Inches Maximum
<b>Locking Feature:</b>	Strip Threads
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Material:</b>	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 303 Overall
<b>Material Document And Classification:</b>	Qq-s-763,cond B Fed Spec 1st Material Response Overall Or Qq-s-763,cond B Fed Spec 2nd Material Response Overall Or Astm A582 Assn Std 3rd Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screwlock from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/642AS7525-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.