

Description

Fastener Length: 3/16", Thread: 4-40, Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	642AS75256
Minimum Qty (MOQ):	30 EA
NSN:	5305-01-080-9170
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel



P/N 642AS7525-6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.106 Inches Minimum And 0.187 Inches Maximum
Fastener Length:	0.156 Inches Minimum And 0.187 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.058 Inches Minimum And 0.068 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 303 Overall
Material Document And Classification:	Qq-s-763,cond B Fed Spec 1st Material Response Overall Or Qq-s-763,cond B Fed Spec 2nd Material Response Overall Or Astm A582 Assn Std 3rd Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screwlock from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/642AS7525-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.