

Description

Fastener Length: 5/16", Thread: 6-32, Thread Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	642AS75492
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-081-0739
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 642AS7549-2 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.136 Inches Minimum And 0.229 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.244 Inches Minimum And 0.279 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Countersink Angle:	82.0 Degrees Nominal
Material:	Plastic Locking Feature
Material:	Steel Comp 4130 Fastener
Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response Fastener
Surface Treatment:	Cadmium Fastener
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 1 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/642AS7549-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.