

**Description**

Fastener Length: 5/16", Thread: 6-32, Thread Length: 7/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	642AS75492
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-081-0739
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N 642AS7549-2 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.136 Inches Minimum And 0.229 Inches Maximum
<b>Fastener Length:</b>	0.281 Inches Minimum And 0.312 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.244 Inches Minimum And 0.279 Inches Maximum
<b>Locking Feature:</b>	Strip Threads
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Countersink Angle:</b>	82.0 Degrees Nominal
<b>Material:</b>	Plastic Locking Feature
<b>Material:</b>	Steel Comp 4130 Fastener
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec Single Material Response Fastener
<b>Surface Treatment:</b>	Cadmium Fastener
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2 Cl 1 Fed Spec Single Treatment Response Fastener
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/642AS7549-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.