

## P/N 655-091-9002

### **Description**

Fastener Length: 1/4", Thread: 6-32, Thread Length: 13/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: 6550919002

Minimum Qty (MOQ): 1 EA

NSN: 5305-00-964-0469

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N 655-091-9002 Specifications**

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.190 Inches Minimum
Fastener Length:	0.250 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.249 Inches Nominal
Locking Feature:	Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Hardness Rating:	64.0 Rockwell B Minimum Overall And 66.0 Rockwell B Maximum Overall
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unc

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/655-091-9002">https://military-fasteners.com/screws/machine+screws/655-091-9002</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.