

P/N 655-113-9006

Description

Fastener Length: 1/8", Thread: 2-56, Thread Length: 1/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: 6551139006

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-052-3715

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N 655-113-9006 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Fastener Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Spline Minor Diameter:	0.038 Inches Nominal
Spline Major Diameter:	0.049 Inches Minimum And 0.050 Inches Maximum
Spline Width:	0.016 Inches Minimum And 0.017 Inches Maximum
Locking Feature:	Strip Threads
Point Style:	Cup
Internal Drive Style:	Four Spline
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Hardness Rating:	45.0 Rockwell C Minimum Fastener And 53.0 Rockwell C Maximum Fastener
Color:	Blue Locking Feature
Material:	Plastic Polychlorotrifluoroethylene Locking Feature
Material:	Steel Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this setscrew from our inventory online by visiting https://military-fasteners.com/screws/setscrews/655-113-9006 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.