

Description

Fastener Length: 1-", Thread: 10-24, Thread Length: 15/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	6555179009
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-619-5567
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 655-517-9009 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.953 Inches Minimum
Fastener Length:	1.000 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.292 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.165 Inches Minimum And 0.180 Inches Maximum
Locking Feature:	Pellet
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Screw Material:	Steel Comp 8630
Locking Feature Material:	Plastic Polyamide
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/655-517-9009> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.