



Military-Fasteners.com

P/N 655-517-9013

Description

Fastener Length: 1-1/2", Thread: 10-24, Thread Length: 1-13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 6555179013 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-020-9572 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N 655-517-9013 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.417 Inches Minimum |
| Fastener Length: | 1.500 Inches Nominal |
| Head Style: | Fillister |
| Head Diameter: | 0.292 Inches Minimum And 0.313 Inches Maximum |
| Head Height: | 0.118 Inches Minimum And 0.130 Inches Maximum |
| Locking Feature: | Pellet Threads |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 24 |
| Material: | Steel Comp 8630 Overall |
| Material Document And Classification: | Mil-s-6050 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/655-517-9013> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.