

## P/N 655-551-9012

## **Description**

Fastener Length: 3/4", Hole Diameter: 3/64", Thread: 10-24, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

6555519012 SKU / Model: 5 EA

Minimum Qty (MOQ):

NSN: 5305-00-151-0357

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N 655-551-9012 Specifications**

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum
Fastener Length:	0.750 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.292 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.123 Inches Minimum And 0.130 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel Comp 1010
Screw Material Document And Classification:	Qq-s-633 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And Ds Style

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/655-551-9012">https://military-fasteners.com/screws/machine+screws/655-551-9012</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.