

Description

6LC-C10 Pin-Rivet Collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	6LCC10
Minimum Qty (MOQ):	10
NSN:	5320-00-551-8002
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N 6LC-C10 Specifications

Collar Outside Diameter:	0.492 Inches Minimum And 0.497 Inches Maximum
Collar Overall Height:	0.250 Inches Minimum And 0.270 Inches Maximum
Lubrication:	Cetyl Alcohol
Collar Inside Diameter:	0.305 Inches Minimum And 0.309 Inches Maximum
Collar Style:	Configural Type
Material:	Aluminum Alloy 2024 Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall Or Mil-c-5541 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1080 Professional/industrial Association Standard

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/6LC-C10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.