

**Description**

rating: 15 amp, klixon 7274 series are small, lightweight, low amperage devices that are specifically designed to protect aircraft/aerospace cable and components in airborne vehicles and equipment.

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	7274215
Minimum Qty (MOQ):	1
NSN:	5925-00-061-3209
ECCN:	EAR99
National Motor Freight:	061300, Circuit Breaker / Switch Noi



\* See page 2 for technical characteristics

# P/N 7274-2-15 Specifications

Body Style:	Single Pole Type
Bushing Length:	0.219 Inches Minimum And 0.281 Inches Maximum
Body Length:	0.719 Inches Minimum And 0.781 Inches Maximum
Body Width:	0.531 Inches Minimum And 0.593 Inches Maximum
Case Material:	Plastic
Center To Center Distance Between Terminals Parallel To Length:	0.672 Inches Minimum And 0.734 Inches Maximum
Fragility Factor:	Moderately Rugged
Mounting Surface To Terminal End Distance:	1.919 Inches Minimum And 1.981 Inches Maximum
Pole Quantity:	1
Arc Quenching Method:	Air
Mounting Facility Type And Quantity:	1 Threaded Bushing W/panel Seal
Storage Type:	General Purpose Warehouse
Thread Quantity Per Inch:	32
Maximum Continuous Load Current Rating Per Pole:	5.0 Amperes Ac Single Location And 5.0 Amperes Dc Single Location
Operating Voltage Type And Rating Per Pole In Volts:	200.0 Ac Single Location And 28.0 Dc Single Location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:	5000.0 Ac Single Location And 5000.0 Dc Single Location
Circuit Protection Type:	Overcurrent Single Location
Trip Release Method:	Thermal Single Location
Trip Release Characteristic:	Time Delay Single Location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:	145.0 Single Location
Reset Method:	Manual
Main Contact Tripping Mechanism Type:	Trip Free
Manual Actuator Type And Quantity:	1 Push-pull
Actuator Function:	Trip-reset
Actuator Position Designation:	At Pole One
Internal Trip Release Configuration:	Series Trip Single Location
Nominal Thread Size:	0.469 Inches
Trip Delay Time In Seconds Per Rated Continuous Current:	2.000 Minimum At 200 Pct Single Location And 20.000 Maximum At 200 Pct Single Location
Inclosure Protection Type For Which Designed:	Vibrationproof And Fungus Resistant And Moisture Resistant
Trip Release Ambient Temp Rating:	25.0 Deg Celsius Nominal Single Location
Frequency In Hertz:	400.0 Single Location

<b>Unpackaged Unit Weight:</b>	38.0 Grams
<b>Thread Series Designator:</b>	Uns
<b>Terminal Type And Quantity:</b>	2 Tab W/screw

## How to Order

Order this circuit breaker from our inventory online by visiting <https://military-fasteners.com/electrical/circuit+breakers/7274-2-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.