

Description

Rating: 4 amp, klixon 7274 series are small, lightweight, low amperage devices that are specifically designed to protect aircraft/aerospace cable and components in airborne vehicles and equipment.

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS26574-4](#)

SKU / Model:	727424
Minimum Qty (MOQ):	1
NSN:	5925-00-733-9243
ECCN:	EAR99
National Motor Freight:	061300, Circuit Breaker / Switch Noi



P/N 7274-2-4 Specifications

Body Style:	Single Pole Type
Bushing Length:	0.359 Inches Nominal
Body Length:	0.744 Inches Nominal
Body Width:	0.562 Inches Nominal
Case Material:	Plastic
Center To Center Distance Between Terminals Parallel To Length:	0.593 Inches Nominal
Mounting Surface To Terminal End Distance:	1.312 Inches Nominal
Pole Quantity:	1
Mounting Facility Type And Quantity:	1 Threaded Bushing
Storage Type:	General Purpose Warehouse
Thread Quantity Per Inch:	32
Maximum Continuous Load Current Rating Per Pole:	4.0 Amperes Ac Single Location And 4.0 Amperes Dc Single Location
Operating Voltage Type And Rating Per Pole In Volts:	120.0 Ac Single Location And 30.0 Dc Single Location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:	800.0 Ac Single Location And 2000.0 Dc Single Location
Circuit Protection Type:	Overcurrent Single Location
Trip Release Method:	Thermal Single Location
Trip Release Characteristic:	Time Delay Single Location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:	145.0 Single Location
Reset Method:	Manual
Main Contact Tripping Mechanism Type:	Trip Free
Manual Actuator Type And Quantity:	1 Push-pull
Actuator Position Designation:	At Pole One
Internal Trip Release Configuration:	Series Trip Single Location
Nominal Thread Size:	0.437 Inches
Trip Delay Time In Seconds Per Rated Continuous Current:	2.000 Minimum At 200 Pct Single Location And 20.000 Maximum At 200 Pct Single Location
Inclosure Protection Type For Which Designed:	Corrosion Resistant And Explosion Proof
Trip Release Ambient Temp Rating:	25.0 Deg Celsius Maximum Single Location
Frequency In Hertz:	60.0 Single Location
Unpackaged Unit Weight:	30.0 Grams
Thread Series Designator:	Un
Terminal Type And Quantity:	2 Tab W/screw

How to Order

Order this circuit breaker from our inventory online by visiting <https://military-fasteners.com/electrical/circuit+breakers/7274-2-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.