P/N 7277-2-3

Description

rating: 3 amps, klixon 7277 series is for applications that do not need the approvals of military circuit breakers. used as primary electrical circuit protection on general aviation aircraft, 7277-2 series breaker

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: 727723

Minimum Qty (MOQ):

NSN: 5925-00-252-4227

ECCN: EAR99

National Motor Freight: 061300, Circuit Breaker / Switch Noi









P/N 7277-2-3 Specifications

Case Material:	Plastic
Pole Quantity:	1
Mounting Facility Type And Quantity:	1 Threaded Bushing
Thread Quantity Per Inch:	32
Maximum Continuous Load Current Rating Per Pole:	3.0 Amperes Ac Single Location And 3.0 Amperes Dc Single Location
Operating Voltage Type And Rating Per Pole In Volts:	120.0 Ac Single Location And 28.0 Dc Single Location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:	-
Circuit Protection Type:	Overcurrent Single Location
Trip Release Method:	Thermal Single Location
Trip Release Characteristic:	Time Delay Single Location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:	150.0 Single Location
Reset Method:	Manual
Main Contact Tripping Mechanism Type:	Trip Free
Manual Actuator Type And Quantity:	1 Push-pull
Actuator Function:	Trip-reset
Internal Trip Release Configuration:	Series Trip Single Location
Nominal Thread Size:	0.438 Inches
Trip Delay Time In Seconds Per Rated Continuous Current:	2.000 Minimum At 200 Pct Single Location And 35.000 Maximum At 200 Pct Single Location
Trip Release Ambient Temp Rating:	25.0 Deg Celsius Nominal Single Location
Thread Series Designator:	Un
Terminal Type And Quantity:	2 Screw

How to Order

Order this circuit breaker from our inventory online by visiting https://military-fasteners.com/electrical/circuit+breakers/7277-2-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.