

Description

Fastener Length: 13/16", Thread: 1/2-18, Thread Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	72991920
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-467-9403
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 72991-9-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.828 Inches Nominal
Fastener Length:	0.828 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.547 Inches Minimum And 0.567 Inches Maximum
Width Between Flats:	0.616 Inches Minimum And 0.627 Inches Maximum
Extended Washer Diameter:	0.928 Inches Minimum And 0.938 Inches Maximum
Extended Washer Thickness:	0.123 Inches Minimum And 0.143 Inches Maximum
Grip Diameter:	0.5605 Inches Minimum And 0.5615 Inches Maximum
Nominal Thread Diameter:	0.562 Inches
Grip Length:	1.250 Inches Nominal
Nonstandard Thread Pitch Diameter:	+0.5354/+0.5359 Inches
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Thread Pitch In Millimeters:	13.3
External Thread Tolerance Class:	2a
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams5662 Assn Std 1st Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,typeii,class2 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/72991-9-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.