

Description

Fastener Length: 4-15/64", Thread: 1/2-18, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	77720956
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-030-1759
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 77720-9-56 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.700 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	4.210 Inches Minimum And 4.240 Inches Maximum
Head Style:	Double Hexagon
Head Height:	0.318 Inches Minimum And 0.338 Inches Maximum
Width Between Flats:	0.865 Inches Minimum And 0.877 Inches Maximum
Grip Diameter:	0.5610 Inches Minimum And 0.5615 Inches Maximum
Nominal Thread Diameter:	0.562 Inches
Grip Length:	3.490 Inches Minimum And 3.510 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	145000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/77720-9-56> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.