

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | 7MLS100M0402 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-276-4921 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE
AVAILABLE

P/N 7MLS100-M04-02 Specifications

| | |
|---|--|
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Head Major Diameter: | 0.188 Inches Minimum And 0.196 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.079 Inches Minimum And 0.125 Inches Maximum |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Material: | Nickel Alloy R-405 Sleeve Or Nickel Alloy 400 Sleeve |
| Material: | Iron Alloy 660 Stem |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Sleeve |
| Surface Treatment: | Passivate Stem |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/7MLS100-M04-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.