

P/N 7S36-3A1

Description

Fastener Length: 27/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: 7S363A1

Minimum Qty (MOQ): 25 EA

NSN: 5305-00-905-4593

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N 7S36-3A1 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Minimum
Fastener Length:	0.408 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.270 Inches Minimum And 0.302 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4130
Screw Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/7S36-3A1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.