

Description

Fastener Length: 27/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 7S363A1 |
| Minimum Qty (MOQ): | 25 EA |
| NSN: | 5305-00-905-4593 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 7S36-3A1 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.338 Inches Minimum |
| Fastener Length: | 0.408 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.270 Inches Minimum And 0.302 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 4130 |
| Screw Material Document And Classification: | Mil-s-6758 Mil Spec Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/7S36-3A1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.