

P/N 7S39-3A7

Military-Fasteners.com

#### Description

Fastener Length: 25/32", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	7S393A7
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-834-8179
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N 7S39-3A7 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.312 Inches Minimum And 0.362 Inches Maximum
Fastener Length:	0.760 Inches Minimum And 0.790 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.297 Inches Minimum And 0.302 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4130
Screw Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

## How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/7S39-3A7</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.