

**Description**

Fastener Length: 27/32", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	7S393A8
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-824-7351
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N 7S39-3A8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.313 Inches Minimum And 0.363 Inches Maximum
<b>Fastener Length:</b>	0.823 Inches Minimum And 0.853 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.297 Inches Minimum And 0.302 Inches Maximum
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1895 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	Mil-s-6758,cond D4 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/7S39-3A8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.