

Description

Fastener Length: 43/64", Thread: 1/4-28, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	7S394A4
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-826-2452
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 7S39-4A4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Fastener Length:	0.660 Inches Minimum And 0.690 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.389 Inches Minimum And 0.394 Inches Maximum
Internal Drive Style:	Cross Recess Type li
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4130
Screw Material Document And Classification:	Mil-s-6758,cond D4 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2class 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/7S39-4A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.