

Description

Diameter: 1/2", steel comp 1008or steel comp 1010or steel comp 1012or steel comp 1015or steel comp 1016or steel comp 1017or steel comp 1018or steel comp 1019or steel comp 1020or steel comp 1021or steel comp 1022or steel comp 1025or steel comp 1030or steel comp 1035or steel comp 1040or steel comp 1045or steel comp 1050or steel comp 1055or steel comp 1060or steel comp 1095 overall

* Manufacturer certifications are shipped with your order FREE of charge

[Order this part online](#)**Additional Information**

SKU / Model:	80S0151AA
Minimum Qty (MOQ):	1 EA
NSN:	5325-00-133-2094
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 80S01-5-1AA Specifications

Grip Length:	0.940 Inches Maximum
Diameter:	0.525 Inches Nominal
Center To Center Distance Between Mounting Holes:	0.873 Inches Minimum And 0.877 Inches Maximum
Mounting Style:	Plain W/mounting Hole
Turnlock Stud Shank Style:	Stud Shank
Turnlock Stud Head Style:	Flat Countersunk
Turnlock Receptacle Style:	Receptacle
Receptacle Overall Length:	1.135 Inches Maximum
Receptacle Height:	0.625 Inches Maximum
Receptacle Width:	0.625 Inches Maximum
Material Accommodated Thickness:	0.431 Inches Minimum And 0.500 Inches Maximum
Drive Type:	Cross Recess
Stud Shank Major Diameter:	0.373 Inches Minimum And 0.375 Inches Maximum
Turnlock Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Material:	Steel Comp 1008 Overall Or Steel Comp 1010 Overall Or Steel Comp 1012 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1017 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1021 Overall Or Steel Comp 1022 Overall Or Steel Comp 1025 Overall Or Steel Comp 1030 Overall Or Steel Comp 1035 Overall Or Steel Comp 1040 Overall Or Steel Comp 1045 Overall Or Steel Comp 1050 Overall Or Steel Comp 1055 Overall Or Steel Comp 1060 Overall Or Steel Comp 1095 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 3 Fed Spec Single Treatment Response Overall

**Nondefinitive Spec/std
Data:**

1 Type

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/80S01-5-1AA> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.