

Description

Diameter: 3/8", steel comp, oval, slotted head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | 821136016 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5325-00-810-5722 |
| Schedule B: | 7318.29.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N 82-11-360-16 Specifications

| | |
|---|--|
| Grip Length: | 0.505 Inches Nominal |
| Diameter: | 0.375 Inches Nominal |
| Securing Device Type: | Ring |
| Turnlock Stud Shank Style: | Stud Shank |
| Turnlock Stud Head Style: | Fillister |
| Material Accommodated Thickness: | 0.350 Inches Minimum And 0.369 Inches Maximum |
| Drive Type: | Slotted |
| Shank Neck Length: | 0.417 Inches Nominal |
| Stud Shank Major Diameter: | 0.240 Inches Nominal |
| Material: | Steel Comp 1008 Overall |
| Material Document And Classification: | Astm A569 Assn Std Single Material Response Overall |
| Surface Treatment: | Chromate Overall And Zinc Overall |
| Surface Treatment Document And Classification: | Mil-c-87115 Mil Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/82-11-360-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.