

Description

Fastener Length: 19/64", Thread: 8-32, Head Width: 5/64", Thread Length: 19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	8803471
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-462-1072
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE
AVAILABLE

P/N 880347-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.295 Inches Minimum And 0.305 Inches Maximum
Fastener Length:	0.295 Inches Minimum And 0.305 Inches Maximum
Head Style:	Headless (setscrew)
Point Length:	0.130 Inches Nominal
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.078 Inches Minimum And 0.079 Inches Maximum
Thread Quantity Per Inch:	32
Point Chamfer Angle:	29.0 Degrees Minimum And 31.0 Degrees Maximum
Special Features:	Two Holes 0.031 In. Min,0.035 In. Max Dia Drilled In Socket Recess,0.045 In. Min,0.055 In. Max Lg From Top Of Recess
Material:	Steel Comp 410 Overall
Material Document And Classification:	Qq-s-766 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/880347-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.