

Description

Fastener Length: 1-1/8", Thread: 10-32, Thread Length: 33/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	8803983
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-498-7623
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 880398-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.460 Inches Minimum And 0.530 Inches Maximum
Fastener Length:	1.110 Inches Minimum And 1.140 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.312 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.610 Inches Minimum And 0.650 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Hardness Rating:	40.0 Rockwell C Minimum Overall And 47.0 Rockwell C Maximum Overall
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams 5643 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/880398-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.