

Description

Fastener Length: 1-11/64", Thread: 8-32, Head Width: 5/64", Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	8875161
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-414-3208
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N 887516-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.360 Inches Minimum And 0.400 Inches Maximum
Fastener Length:	1.150 Inches Minimum And 1.180 Inches Maximum
Grip Diameter:	0.1580 Inches Minimum And 0.1585 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.750 Inches Minimum And 0.820 Inches Maximum
Width Across Flats:	0.078 Inches Minimum And 0.080 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Iron Alloy 660 Overall
Thread Series Designator:	Unc

How to Order

Order this screw sch cap from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/887516-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.