

Description

Fastener Length: 1-1/8", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	8877382
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-385-3380
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 887738-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.340 Inches Minimum
Fastener Length:	1.120 Inches Minimum And 1.140 Inches Maximum
Head Style:	Hexagon
Head Height:	0.260 Inches Minimum And 0.290 Inches Maximum
Width Between Flats:	0.312 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Hardness Rating:	40.0 Rockwell C Minimum Overall And 47.0 Rockwell C Maximum Overall
Countersink Angle:	59.0 Degrees Minimum And 61.0 Degrees Maximum
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams 5643 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shoulder bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/887738-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.