

Description

Thread: 1/4-24, Thread Length: 1-19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 966304 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-207-7439 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N 9-66304 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.300 Inches Minimum |
| Distance From Inside Center Of Bend To Bolt End: | 1.755 Inches Nominal |
| Inside Distance Between Shanks: | 0.630 Inches Nominal |
| Nominal Thread Diameter: | 0.312 Inches |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 150000 Pounds Per Square Inch |
| Material: | Steel Comp 8630 Overall Or Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall |
| Style Designator: | Square Bend |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/9-66304> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.