

Description

Fastener Length: 5/16", Thread: 8-32, Thread Length: 13/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 902660 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-00-518-5610 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 902660 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.119 Inches Minimum And 0.212 Inches Maximum |
| Fastener Length: | 0.281 Inches Minimum And 0.312 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.300 Inches Minimum And 0.332 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Screw Material: | Steel |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/902660> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.