

Description

Fastener Length: 9/16", Thread: 2-56, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	940D33328
Minimum Qty (MOQ):	200 EA
NSN:	5305-00-151-5795
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 940D333-28 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.495 Inches Minimum And 0.562 Inches Maximum
Fastener Length:	0.531 Inches Minimum And 0.562 Inches Maximum
Head Style:	Pan
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.062 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s: Aircraft, Stratofortress B-52; Family Of Medium Tactical Vehicles-medium; Helicopter, Mh-53e; Helicopter, Electronic Countermeasures, Eh-60a; Helicopter, Observation (ahip), Oh-58d; Aircraft, B-2 Bomber (atb); Helicopter, Seahawk, H-60; Helicopter, Iroquois Uh-1; Helicopter, Advance Attack, Ah-1w
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-634 Fed Spec Single Material Response Or Qq-s-637 Fed Spec Single Material Response Or 66 Fed Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 9c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/940D333-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.