

P/N 953527-487

Description

Fastener Length: 3/4", Thread: 10-32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: 953527487

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-027-1225

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N 953527-487 Specifications

| Thread Class: | 3a |
|---------------------------------------|--|
| Thread Direction: | Right-hand |
| Fastener Length: | 0.812 Inches Nominal |
| Head Style: | Double Hexagon Extended Washer |
| Head Height: | 0.250 Inches Minimum And 0.270 Inches Maximum |
| Width Between Flats: | 0.277 Inches Nominal |
| Extended Washer Diameter: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Extended Washer Thickness: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Mil-s-8879 Mil Spec Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/953527-487 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/953527-487 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/953527-487 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/953527-487 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/machine+screws/953527-487 and selecting the quantity you want then cart in the property of t