

P/N 953528-120

Description

Fastener Length: 1/2", Hole Diameter: 3/64", Thread: 8-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: 953528120

Minimum Qty (MOQ): 1 EA

NSN: 5305-00-394-5349

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N 953528-120 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.500 Inches Nominal
Head Style:	Double Hexagon W/ Hole
Head Height:	0.240 Inches Minimum And 0.260 Inches Maximum
Width Between Flats:	0.220 Inches Maximum
Extended Washer Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Extended Washer Thickness:	0.040 Inches Maximum
Hole Diameter:	0.040 Inches Nominal
Nominal Thread Diameter:	0.164 Inches
Hole Quantity:	4
Thread Quantity Per Inch:	32
Screw Material:	Steel Corrosion Resisting
Head Hole Configuration Style:	Hexagon Longitudinal Hole
Thread Series Designator:	Unjc

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/953528-120 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.