

## P/N 953528-530

### **Description**

Fastener Length: 1-17/32", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 1-"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: 953528530

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-512-5799

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N 953528-530 Specifications

L	
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.000 Inches Nominal
Fastener Length:	1.484 Inches Minimum And 1.531 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.320 Inches Minimum And 0.340 Inches Maximum
Width Between Flats:	0.304 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.428 Inches Minimum And 0.448 Inches Maximum
Extended Washer Thickness:	0.060 Inches Minimum And 0.070 Inches Maximum
Hole Diameter:	0.032 Inches Minimum And 0.042 Inches Maximum
End Item Identification:	F100/220 Eng
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.500 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Part Name Assigned By Controlling Agency:	Screw,machine 12 Point
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams 5643 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/953528-530">https://military-fasteners.com/bolts/machine+bolts/953528-530</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.