

**Description**

Fastener Length: 25/64", Thread: 4-40, Head Width: 3/32", Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	965811155C
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-308-1540
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N 965811-155C Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.309 Inches Minimum And 0.391 Inches Maximum
<b>Fastener Length:</b>	0.359 Inches Minimum And 0.391 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.176 Inches Minimum And 0.183 Inches Maximum
<b>Head Height:</b>	0.108 Inches Minimum And 0.112 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Width Across Flats:</b>	0.093 Inches Minimum And 0.095 Inches Maximum
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/965811-155C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.