

Description

Fastener Length: 45/64", Thread: 8-32, Head Width: 9/64", Thread Length: 45/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	965811260C
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-372-9975
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 965811-260C Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.610 Inches Minimum And 0.704 Inches Maximum
Fastener Length:	0.672 Inches Minimum And 0.704 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/965811-260C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.