

Description

Fastener Length: 1-5/64", Thread: 8-32, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------|
| SKU / Model: | 9742291 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-00-492-0317 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N 974229-1 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.290 Inches Minimum And 0.330 Inches Maximum |
| Fastener Length: | 1.070 Inches Minimum And 1.090 Inches Maximum |
| Head Style: | Hexagon Countersunk |
| Head Height: | 0.120 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.312 Inches Nominal |
| Grip Diameter: | 0.1604 Inches Minimum And 0.1607 Inches Maximum |
| Nominal Thread Diameter: | 0.164 Inches |
| Grip Length: | 0.542 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 40.0 Rockwell C Minimum Overall And 47.0 Rockwell C Maximum Overall |
| Hardness Rating: | 40.0 Rockwell C Minimum And 47.0 Rockwell C Maximum Overall |
| Countersink Angle: | 58.0 Degrees Minimum And 60.0 Degrees Maximum |
| iii Part Name Assigned By Controlling Agency: | Navy Special Project |
| Special Features: | Relief Groove Under Head 0.040 In. Max Lg By 0.151 In. Nom Dia |
| Material: | Steel Comp 630 Overall |
| Material Document And Classification: | Ams 5643 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this screw shldr from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/974229-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.