

Description

Fastener Length: 1-5/64", Thread: 8-32, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	9742291
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-492-0317
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N 974229-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.290 Inches Minimum And 0.330 Inches Maximum
Fastener Length:	1.070 Inches Minimum And 1.090 Inches Maximum
Head Style:	Hexagon Countersunk
Head Height:	0.120 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.312 Inches Nominal
Grip Diameter:	0.1604 Inches Minimum And 0.1607 Inches Maximum
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.542 Inches Nominal
Thread Quantity Per Inch:	32
Hardness Rating:	40.0 Rockwell C Minimum Overall And 47.0 Rockwell C Maximum Overall
Hardness Rating:	40.0 Rockwell C Minimum And 47.0 Rockwell C Maximum Overall
Countersink Angle:	58.0 Degrees Minimum And 60.0 Degrees Maximum
iii Part Name Assigned By Controlling Agency:	Navy Special Project
Special Features:	Relief Groove Under Head 0.040 In. Max Lg By 0.151 In. Nom Dia
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams 5643 Assn Std Single Material Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw shldr from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/974229-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.