

**Description**

Diameter: 1/2", steel comp 1010 overall

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	982652230
Minimum Qty (MOQ):	1
NSN:	5325-01-191-0335
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 98265-2-230 Specifications

<b>Grip Length:</b>	0.417 Inches Minimum And 0.427 Inches Maximum
<b>Diameter:</b>	0.562 Inches Nominal
<b>Securing Device Type:</b>	Spring
<b>Turnlock Stud Shank Style:</b>	Stud Shank
<b>Turnlock Stud Head Style:</b>	Flat Countersunk
<b>Material Accommodated Thickness:</b>	0.221 Inches Minimum And 0.230 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Stud Shank Major Diameter:</b>	0.262 Inches Minimum And 0.267 Inches Maximum
<b>Material:</b>	Steel Comp 1010 Overall
<b>Material Document And Classification:</b>	Sae Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/98265-2-230> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.