

**Description**

Diameter: 1/2", steel overall

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	982656630
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-281-6224
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi

NO IMAGE  
AVAILABLE

## P/N 98265-6-630 Specifications

<b>Grip Length:</b>	0.817 Inches Minimum And 0.827 Inches Maximum
<b>Diameter:</b>	0.560 Inches Nominal
<b>Turnlock Stud Shank Style:</b>	Stud Shank
<b>Turnlock Stud Head Style:</b>	Flat Countersunk
<b>Material Accommodated Thickness:</b>	0.621 Inches Minimum And 0.630 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Stud Shank Major Diameter:</b>	0.262 Inches Minimum And 0.268 Inches Maximum
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall

## How to Order

Order this stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/98265-6-630> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.