

## P/N 98265-6-630

### **Description**

Diameter: 1/2", steel overall

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	982656630
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-281-6224
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N 98265-6-630 Specifications

Grip Length:	0.817 Inches Minimum And 0.827 Inches Maximum
Diameter:	0.560 Inches Nominal
Turnlock Stud Shank Style:	Stud Shank
Turnlock Stud Head Style:	Flat Countersunk
Material Accommodated Thickness:	0.621 Inches Minimum And 0.630 Inches Maximum
Drive Type:	Slotted
Stud Shank Major Diameter:	0.262 Inches Minimum And 0.268 Inches Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall

## **How to Order**

Order this stud from our inventory online by visiting <a href="https://military-fasteners.com/studs/turnlock+fastener+studs/98265-6-630">https://military-fasteners.com/studs/turnlock+fastener+studs/98265-6-630</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.