

Description

Length: 19/64", 99785 series pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	997852
Minimum Qty (MOQ):	25
NSN:	5315-00-141-6355
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



P/N 99785-2 Specifications

First End Style:	Radius
Overall Length:	0.307 Inches Minimum And 0.317 Inches Maximum
Intermediate Diameter:	0.0675 Inches Minimum And 0.0697 Inches Maximum
First End Corner Radius:	0.015 Inches Nominal
Features Provided:	Casehardened
Second End Relationship With First End:	Identical
Pin Small End Diameter:	0.0600 Inches Minimum And 0.0615 Inches Maximum
First End Location:	Both Ends
Special Features:	Serrations Must Be 0.160 In. Lg
Material:	Steel Comp 6150 Overall
Material Document And Classification:	Sae Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	Center Groove

How to Order

Order this grooved headless pin from our inventory online by visiting <https://military-fasteners.com/pins/grooved+headless+pins/99785-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.