

Description

Thread Size: 3/16", Nut Length: 45/64", anodize surface, fine thread, Rivnut A10 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS27130-A28](#) [NAS1329A3-230](#) [AEA10-230](#)

SKU / Model:	A10230
Minimum Qty (MOQ):	25
NSN:	5310-00-225-8360
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N A10-230 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.391 Inches Minimum And 0.421 Inches Maximum
Head Height:	0.033 Inches Minimum And 0.043 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.688 Inches Minimum And 0.718 Inches Maximum
Err Default:	+0.180/+0.230 Inches
Unable To Decode:	+0.180 To 0.230 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Aluminum Alloy 6053 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/A10-230> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.