

Description

Toggle Switch

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | A223S1YZQ |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5930-01-341-7938 |
| ECCN: | EAR99 |
| National Motor Freight: | 061300, Circuit Breaker / Switch Noi |



* See page 2 for technical characteristics

P/N A223S1YZQ Specifications

| | |
|--|--|
| Thread Class: | 2a |
| Body Style: | Bushing Mount |
| Overall Length: | 0.450 Inches Nominal |
| Overall Height: | 1.247 Inches Minimum And 1.287 Inches Maximum |
| Overall Width: | 0.500 Inches Nominal |
| Bushing Length: | 0.342 Inches Minimum And 0.362 Inches Maximum |
| Body Length: | 0.450 Inches Nominal |
| Body Width: | 0.500 Inches Nominal |
| Body Height: | 0.410 Inches Nominal |
| Case Material: | Metal |
| Actuator Style: | Round |
| Actuator Diameter: | 0.105 Inches Minimum And 0.125 Inches Maximum |
| Actuator Height: | 0.400 Inches Minimum And 0.420 Inches Maximum |
| Actuator Position-action Relationship: | Up Position Maintained And Down Position Maintained |
| Maximum Voltage Rating In Volts: | 28.0 Dc And 250.0 Ac |
| Inclosure Type: | Fully Inclosed |
| Mounting Method: | Threaded Bushing |
| Thread Quantity Per Inch: | 40 |
| Nominal Thread Size: | 0.250 Inches |
| Nonpile-up Contact Arrangement: | 2 Pole, Double Throw, Both Positions Maintained Single Switch Unit |
| Contact Load Current Rating At Maximum Rated Voltage: | 6.000 Amperes Resistive Dc And 3.000 Amperes Resistive Ac |
| Precious Material And Location: | Contact And Terminal Surfaces Silver |
| Thread Series Designator: | Uns |
| Terminal Type And Quantity: | 6 Tab, Solder Lug |

How to Order

Order this toggle switch from our inventory online by visiting <https://military-fasteners.com/electrical/toggle+switches/A223S1YZQ> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.