

Description

Fastener Length: 25/32", Thread: 4-11/16-, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	A253C
Minimum Qty (MOQ):	35 EA
NSN:	5305-00-437-4287
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N A25-3C Specifications

Thread Direction:	Right-hand
Thread Length:	0.410 Inches Minimum And 0.490 Inches Maximum
Fastener Length:	0.750 Inches Minimum And 0.790 Inches Maximum
Head Style:	Hexagon
Head Height:	0.106 Inches Minimum And 0.113 Inches Maximum
Width Between Flats:	0.319 Inches Minimum And 0.324 Inches Maximum
Nominal Thread Diameter:	4.7 Millimeters
Thread Pitch In Millimeters:	0.81
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Bs S.114 Fed Std Single Material Response Or Bs S.95 Fed Std Single Material Response Or Bs S.94 Fed Std Single Material Response Or Bs S. 96 Fed Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	D.t.d.904,fscm 05901 Mfr Ref Single Treatment Response
Thread Series Designator:	Ba

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/A25-3C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.