

**Description**

Fastener Length: 25/32", Thread: 4-11/16-, Thread Length: 31/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	A253C
Minimum Qty (MOQ):	35 EA
NSN:	5305-00-437-4287
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N A25-3C Specifications

<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.410 Inches Minimum And 0.490 Inches Maximum
<b>Fastener Length:</b>	0.750 Inches Minimum And 0.790 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.106 Inches Minimum And 0.113 Inches Maximum
<b>Width Between Flats:</b>	0.319 Inches Minimum And 0.324 Inches Maximum
<b>Nominal Thread Diameter:</b>	4.7 Millimeters
<b>Thread Pitch In Millimeters:</b>	0.81
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Screw Material Document And Classification:</b>	Bs S.114 Fed Std Single Material Response Or Bs S.95 Fed Std Single Material Response Or Bs S.94 Fed Std Single Material Response Or Bs S. 96 Fed Std Single Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	D.t.d.904,fscm 05901 Mfr Ref Single Treatment Response
<b>Thread Series Designator:</b>	Ba

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/A25-3C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.