

Description

Diameter: 9/16", steel overall

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[2501-20-29-C3C](#)

| | |
|-------------------------|--|
| SKU / Model: | A5T29 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-00-837-9124 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N A5T29 Specifications

| | |
|---|---|
| Grip Length: | 0.590 Inches Nominal |
| Diameter: | 0.557 Inches Minimum And 0.562 Inches Maximum |
| Turnlock Stud Shank Style: | Stud Shank |
| Turnlock Stud Head Style: | Fillister |
| Material Accommodated Thickness: | 0.281 Inches Minimum And 0.290 Inches Maximum |
| Drive Type: | Slotted |
| Shank Neck Length: | 0.370 Inches Nominal |
| Stud Shank Major Diameter: | 0.306 Inches Minimum And 0.311 Inches Maximum |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/A5T29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.