

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | AAC0502 |
| Minimum Qty (MOQ): | 255 EA |
| NSN: | 5320-01-014-7507 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AAC-05-02 Specifications

| | |
|-----------------------------|--|
| Fastener Length: | 0.300 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.263 Inches Nominal |
| Expansion Device: | Plain Stem-type T |
| Grip Length: | 0.062 Inches Minimum And 0.125 Inches Maximum |
| Shear Strength: | 325 Single Pounds Per Square Inch |
| Countersink Angle: | 120.0 Degrees Nominal |
| Material: | Aluminum Alloy 5052 Body |
| Material: | Aluminum Alloy 7178 Mandrel |

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AAC-05-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.