

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AAC0502
Minimum Qty (MOQ):	255 EA
NSN:	5320-01-014-7507
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N AAC-05-02 Specifications

Fastener Length:	0.300 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Self-plugging
Head Major Diameter:	0.263 Inches Nominal
Expansion Device:	Plain Stem-type T
Grip Length:	0.062 Inches Minimum And 0.125 Inches Maximum
Shear Strength:	325 Single Pounds Per Square Inch
Countersink Angle:	120.0 Degrees Nominal
Material:	Aluminum Alloy 5052 Body
Material:	Aluminum Alloy 7178 Mandrel

How to Order

Order this pop rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/AAC-05-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.